



# ROTASLASHER

HS/HSR  
34/150  
34/180

A heavy-duty performer, HS 34 is equally suitable for road-side and plantations maintenance as for undergrowth clearing.


Fitted with clutch protection, this machine is capable of slashing bushes and small trees. Heavy-duty blades, mounted in hardened journal - swing back if hitting major objects. Universal PTO drive shaft with clutch.



Blade



Beam



PTO Drive Shaft



Model	HS/HSR	HS34/150	HSR34/150	HS34/180	HSR34/180
Dimension, mm (L x W x H)		1717 x 1713 x 1015	2030 x 1713 x 1015	2012 x 1967 x 1050	2325 x 1967 x 1050
Working Width, cm		150		180	
For Tractor, Hp		60-90hp		70-95hp	
3-Point Linkage, CAT		I/II			
Universal Driveshaft		A6 c/w FF2 Slip Clutch			
Blade Speed at 540 rpm		778			
Cutting Heights, cm		1 - 10			
No of Blades		2			
Size of Blades, mm		75 x 12			
With Front and Rear Roller		NO	YES	NO	YES
Type of Blade		Cranked and Swing			
Weight (kg)		300	340	380	440

ISO 9001:2015 CERTIFIED

ACCREDITED BY SIRIM QAS

**HOWARD Alatpertanian Sdn. Bhd.**  
(Co. No. 30189-A)  
No. 2, Jalan Tiga - Batu 20,  
48000 Rawang,  
Selangor D.E.

No. Tel : 03-60931010  
No. Fax : 03-60921010  
E-mail : [howard@howardmy.com](mailto:howard@howardmy.com)  
Website : [www.howardmy.com](http://www.howardmy.com)